## NSN 5935-00-804-2800

Electrical Receptacle Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-00-804-2800               |
|---|
| Thread Class:   |
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Body Style:   |
| Straight shape, external coupling   |
| Overall Length:   |
| 1.531 inches  |
| Overall Height:   |
| 2.000 inches  |
| Overall Width:  |
| 2.000 inches  |
| Environmental Protection:   |
| Watertight  |
| Unthreaded Mounting Hole Diameter:  |
| Between 0.145 inches and 0.151 inches                                       |
| Center To Center Distance Between Mounting Facilities Parallel To Height:   |
| Between 1.557 inches and 1.567 inches                                       |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 1.557 inches and 1.567 inches                                       |
| Distance From Mounting Shoulder To Front Face:                              |
| Between 0.812 inches and 0.822 inches                                       |
| Threaded Device Type:   |
| Coupling facility   |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 28-21 single mating end   |
| Contact Removability:   |
| Removable single mating end single contact grouping                         |
| Contact Maximum Current Rating In Amps:                                     |
| 13.0 single mating end single contact grouping                              |
| Contact Maximum Ac Voltage Rating In Volts:                                 |
| 500.0 single mating end single contact grouping                             |
| Contact Maximum Dc Voltage Rating In Volts:                                 |
| 700.0 single mating end single contact grouping                             |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Externally threaded shell   |
| Thread Length:  |

0.625 inches

## NSN 5935-00-804-2800

Electrical Receptacle Connector - Page 2 of 2



| Thready Qty Per Inch (tpi):   |
|---|
| 18  |
| Thread Size:  |
| 1.750 inches  |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material:  |
| Rubber single mating end  |
| Terminal Type:  |
| Crimp single mating end single contact grouping   |
| Shell Material:   |
| Aluminum alloy  |
| Shell Surface Treatment:  |
| Cadmium and chromate  |
| Included Contact Quantity:  |
| 37 single mating end single contact grouping  |
| Included Contact Type:  |
| Round socket single mating end single contact grouping  |
| Precious Material And Location:   |
| Contact surfaces gold and contact surfaces silver   |
| Precious Material And Weight:   |
| 0.037 gold grains, troy and 0.037 silver grains, troy   |
| Precious Material:  |
| Gold and silver   |
| Thread Series Designator:   |
| Uns   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A039b0  |
|   |