

View Online at <https://aerobasegroup.com/nsn/5935-00-804-2812>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

0.875 inches

Overall Height:

0.469 inches

Overall Width:

Between 0.333 inches and 0.353 inches

Distance Between Mounting Facility Centers:

0.625 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping and gold single mating end single contact grouping

Insert Material:

Plastic melamine single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification 1st treatment response single mating end single contact grouping and mil-g-45204 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-746 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-p-14d, ty mme military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver and contact surfaces gold

Precious Material And Weight:

0.011 silver grains, troy and 0.011 gold grains, troy

Precious Material:

Silver and gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.