Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-804-2812

Thread Class:
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
0.875 inches
Overall Height:
0.469 inches
Overall Width:
Between 0.333 inches and 0.353 inches
Distance Between Mounting Facility Centers:
0.625 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping and gold single mating end single contact grouping
Insert Material:
Plastic melamine single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification 1st treatment response single mating end single contact grouping and mil-g-45204 military specification 2nd

treatment response single mating end single contact grouping



Solder well s	ingle mating end single contact grouping
Contact Mat	erial Specification:
Qq-b-746 fec	leral specification single material response single mating end single contact groupi
Insert Mater	ial Specification:
Mil-p-14d, ty	mme military specification single material response single mating end
Unable To D	ecode:
Unable to de	code and unable to decode
Included Co	ntact Quantity:
11 single ma	ting end single contact grouping
Included Co	ntact Type:
Round socke	t single mating end single contact grouping
Precious Ma	terial And Location:
Contact surfa	aces silver and contact surfaces gold
Precious Ma	terial And Weight:
0.011 silver g	grains, troy and 0.011 gold grains, troy
Precious Ma	iterial:
Silver and go	ld
Thread Serie	es Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Meas	sure:
Demilitarizat	tion:
No	
Fiig:	
A039b0	
Mil-std (milit	tary Standard):
Mil-g-45204 :	spec.