NSN 5935-00-804-5144

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-804-5144 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.188 inches **Overall Height:** 0.500 inches **Overall Width:** 0.500 inches **Environmental Protection:** Moisture resistant **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Frequency Rating:** 4000.0 megahertz single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

NSN 5935-00-804-5144

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic polytetrafluoroethylene single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Nickel
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surface silver
Precious Material And Weight:
0.005 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0