

View Online at <https://aerobasegroup.com/nsn/5935-00-804-5815>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.703 inches

**Overall Diameter:**

0.812 inches

**Environmental Protection:**

Pressure proof and corrosion resistant

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Bnc 2nd mating end

**Contact Removability:**

Removable all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

1500.0 all mating ends all contact groupings

**Shell Type:**

Armored

**Connector Locking Method:**

Shell twistlock

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends all contact groupings

**Thread Length:**

0.594 inches

**Thread Size:**

0.625 inches

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:**

Silver all mating ends all contact groupings

**Insert Material:**

Plastic tetrafluoroethylene all mating ends

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Included Contact Quantity:**

2 all mating ends single contact grouping

**Included Contact Type:**

Coaxial socket all mating ends all contact groupings

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.068 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0