

View Online at <https://aerobasegroup.com/nsn/5935-00-805-0622>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape threaded

Overall Length:

0.825 inches

Overall Diameter:

Between 1.359 inches and 1.391 inches

Environmental Protection:

Moisture proof and salt water resistant

Distance From Mounting Shoulder To Front Face:

Between 0.696 inches and 0.721 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.125 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

14-18 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Size:

1.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Nickel single mating end single contact grouping

Contact Surface Treatment:

Tin single mating end single contact grouping

Insert Material:

Glass single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Lacquer

Included Contact Quantity:

18 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Hermtically sealed

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0