NSN 5935-00-805-2843

Body Style: Angle shape

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-805-2843

Overall Length:
2.500 inches
Overall Height:
3.219 inches
Cable Entrance Diameter:
Between 0.573 inches and 0.656 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Solid Connector Locking Method:
Connector Locking Method:
Connector Locking Method: Screw
Connector Locking Method: Screw Connector Cable Strain Relief Method:
Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp
Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Terminal Location:
Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Terminal Location: Side single mating end single contact grouping
Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Terminal Location: Side single mating end single contact grouping Contact Material:
Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Terminal Location: Side single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Terminal Location: Side single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:
Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Terminal Location: Side single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping
Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Terminal Location: Side single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material:
Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Terminal Location: Side single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum
Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Terminal Location: Side single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum Included Contact Quantity:
Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Terminal Location: Side single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum Included Contact Quantity: 30 single mating end single contact grouping
Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Terminal Location: Side single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum Included Contact Quantity: 30 single mating end single contact grouping Included Contact Type:

NSN 5935-00-805-2843

Electrical Plug Connector - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A039b0