

View Online at <https://aerobasegroup.com/nsn/5935-00-805-3463>

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

3.000 inches

Overall Diameter:

0.938 inches

Cable Entrance Diameter:

0.438 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

5 number 20 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate mineral filled single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Chromium

Included Contact Quantity:

5 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.005 gold grains, troy and 0.005 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0