NSN 5935-00-806-2683

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-806-2683 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.710 inches **Overall Diameter:** 0.313 inches **Environmental Protection:** Salt water resistant and corrosion resistant **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin Radio Frequency Type Contact Characteristic Impedance In Ohms: 93.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 32 Thread Size: 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic tetrafluoroethylene single mating end **Terminal Type:** Turret single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:**

Silver

NSN 5935-00-806-2683

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and shell surface silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.100 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a

Demilitarization:

Unit Of Measure:

No

Fiig:

A039b0