NSN 5935-00-806-5534

Thread Class:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-806-5534

Inread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Angle shape, w/o cable clamp
Overall Diameter:
1.469 inches
Body Angle In Deg:
90.0
Environmental Protection:
Fireproof
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20-2006-41 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
41.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Distance From Centerline To Connector End:
2.594 inches
Distance From Centerline To Cable End:
1.656 inches
Thread Length:
0.375 inches and 0.719 inches
Operating Tempurature Rating:
050 0 de sue en feloueur heit

350.0 degrees fahrenheit

NSN 5935-00-806-5534Electrical Plug Connector - Page 2 of 2



Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.188 inches and 1.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic melamine single mating end and glass fiber single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.020 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0