NSN 5935-00-806-7509

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-806-7509

Body Style:
Straight shape
Unable To Decode:
Unable to decode and unable to decode and unable to decode
Overall Length:
1.468 inches
Overall Height:
3.349 inches
Overall Width:
1.125 inches
Environmental Protection:
Pressure proof
Unthreaded Mounting Hole Diameter:
0.143 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 2.899 inches and 2.909 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.497 inches and 0.503 inches
Distance From Mounting Shoulder To Front Face:
0.396 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
59 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end 2nd contact grouping
Contact Maximum Dc Voltage Rating In Volts:
600.0 single mating end all contact groupings
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:

Rhodium single mating end all contact groupings and silver single mating end all contact groupings

Plastic diallyl phthalate single mating end

Insert Material:

NSN 5935-00-806-7509

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Chromate
Insert Material Specification:
Mil-m-14, type mdg military specification single material response single mating end
Included Contact Quantity:
57 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end 2nd contact grouping
Special Features:
Furnished items - spring and washer and mounting nut
Precious Material And Location:
Contact surfaces rhodium and contact surfaces silver
Precious Material And Weight:
0.059 rhodium grains, troy and 0.059 silver grains, troy
Precious Material:
Rhodium and silver
Test Data Document:
81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-5015 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.