## NSN 5935-00-806-8588

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-806-8588 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape quick connect **Overall Length:** Between 2.276 inches and 2.286 inches **Overall Width:** Between 0.557 inches and 0.567 inches **Environmental Protection:** Hermetic and weatherproof **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Dm all mating ends **Contact Removability:** Nonremovable all mating ends single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 140.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.437 inches **Contact Material:** Copper alloy all mating ends single contact grouping **Contact Surface Treatment:** Gold all mating ends single contact grouping and silver all mating ends single contact grouping **Insert Material:** Plastic tetrafluoroethylene all mating ends **Shell Material:** Copper alloy

**Included Contact Quantity:** 

1 all mating ends single contact grouping

## NSN 5935-00-806-8588

Connector Adapter - Page 2 of 2



Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial pin all mating ends single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
$0.010 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.010 \ \text{silver grains}, \ \text{troy}$
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0