NSN 5935-00-807-0052

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-807-0052 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 2.181 inches **Overall Height:** 1.281 inches **Overall Width:** 1.281 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.130 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.969 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.969 inches **Distance From Mounting Shoulder To Front Face:** Between 0.750 inches and 0.781 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16s-1 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0

Shell Type:

Solid

NSN 5935-00-807-0052

A039b0

Electrical Receptacle Connector - Page 2 of 2



| Connector Locking Method: |
|--|
| Externally threaded shell |
| Thread Length: |
| 0.625 inches |
| Thread Size: |
| 1.000 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material: |
| Rubber single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Included Contact Quantity: |
| 7 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Special Features: |
| 4 mtg holes |
| Precious Material And Location: |
| Contact surface gold and contact surface silver |
| Precious Material: |
| Gold and silver |
| Test Data Document: |
| 81349-milc5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fila: |