Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-807-0162

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape Overall Length:
1.563 inches
Overall Height:
0.859 inches
Overall Width:
0.438 inches
Environmental Protection:
Salt water resistant and shock proof and vibration resistant
Distance Between Mounting Facility Centers:
1.250 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1 Contact Regittion Arrowment Styles
Contact Position Arrangement Style:
20 20-20 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Screw
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic single mating end

NSN 5935-00-807-0162 Electrical Receptacle Connector - Page 2 of 2



Terminal Type: Crimp single mating end single contact grouping **Included Contact Quantity:** 20 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0