Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-807-0808

Body Style:

Hood, top opening, w/clamp

Overall Length:

1.721 inches

Overall Height:

1.987 inches

Overall Width:

1.275 inches

Environmental Protection:

Vibration resistant

Cable Entrance Diameter:

0.312 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

8 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

800.0 single mating end single contact grouping

Polarization Method:

Shell

Shell Type:

Hood, top opening

Connector Locking Method:

Latch

Connector Cable Strain Relief Method:

Cable clamp

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-00-807-0808 Electrical Plug Connector - Page 2 of 2



Tab,	solder lug single mating end single contact grouping
Shell	Material:
Coppe	er alloy
Shell	Surface Treatment:
Nickel	
Insert	Material Specification:
Mil-m-	14, ty sdg military specification single material response single mating end
Shell	Guide Type And Location Designator:
A pin a	and 2 pin
Includ	led Contact Quantity:
8 sing	le mating end single contact grouping
Includ	led Contact Type:
Leaf s	pring single mating end single contact grouping
Precie	ous Material And Location:
Conta	ct surfaces gold
Precie	ous Material And Weight:
0.008	gold grains, troy
Precie	ous Material:
Gold	
Shelf	Life:
N/a	
Unit C	Of Measure:
Demil	itarization:
No	
Fiig:	
A039b	0
Mil-st	d (military Standard):
	45204 spec.