Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-807-7166

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
1.562 inches
Overall Diameter:
1.312 inches
Environmental Protection:
Pressure proof
Distance From Mounting Shoulder To Front Face:
1.219 inches
Mounting Facility Thickness:
0.250 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
16-10 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
41.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Length:
1.219 inches
Thready Qty Per Inch (tpi):
20 and 20

NSN 5935-00-807-7166

Electrical Receptacle Connector - Page 2 of 2



1 000 inch	es and 1.000 inches
Terminal	
	e mating end single contact grouping
Contact N	
	oy single mating end single contact grouping
	Surface Treatment:
	e mating end single contact grouping and silver single mating end single contact groupir
Insert Mat	
	gle mating end
Terminal	
	Il single mating end single contact grouping
Shell Mate	
Aluminum	
	ace Treatment:
Anodize	
	Contact Quantity:
	ating end single contact grouping
	Accommodation Hole Shape:
Round w/c	-
Included	Contact Type:
	cket single mating end single contact grouping
Precious	Material And Location:
Contact su	Irfaces gold and contact surfaces silver
	Material And Weight:
0.015 gold	l grains, troy and 0.015 silver grains, troy
Precious	Material:
Gold and	silver
Thread Se	eries Designator:
Unef and u	unef
Shelf Life	:
N/a	
Unit Of M	easure:
Demilitari	zation:
No	
Fiig:	
A039b0	