NSN 5935-00-809-2354

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-809-2354 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.562 inches and 1.602 inches **Overall Height:** 1.500 inches **Overall Width:** 1.500 inches **Unthreaded Mounting Hole Diameter:** Between 0.118 inches and 0.124 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** Between 0.740 inches and 0.750 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 20-27 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

NSN 5935-00-809-2354

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):
18
Thread Size:
1.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Anodize
Included Contact Quantity:
14 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0