# NSN 5935-00-810-3699

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-810-3699

**Body Style:** 

Straight shape

**Overall Length:** 

Between 1.109 inches and 1.141 inches

**Overall Height:** 

Between 1.109 inches and 1.141 inches

**Overall Width:** 

Between 2.296 inches and 2.328 inches

**Unthreaded Mounting Hole Diameter:** 

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.062 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.324 inches and 0.360 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

13 single mating end

**Contact Removability:** 

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end 2nd contact grouping

**Polarization Method:** 

Shell

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end all contact groupings and silver single mating end all contact groupings

**Insert Material:** 

Plastic melamine single mating end

**Terminal Type:** 

Solder well single mating end all contact groupings

**Shell Material:** 

Aluminum

# NSN 5935-00-810-3699

Electrical Receptacle Connector - Page 2 of 2



#### **Shell Surface Treatment:**

Cadmium and chromate

### **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

### **Shell Material Specification:**

Qq-a-591, comp 10 federal specification single material response

### **Insert Material Specification:**

Mil-m-14, ty mme military specification single material response single mating end

### **Included Contact Quantity:**

12 single mating end 2nd contact grouping

#### **Included Contact Type:**

Round pin single mating end 2nd contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

### **Precious Material And Weight:**

0.012 gold grains, troy and 0.012 silver grains, troy

#### **Precious Material:**

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

### Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-m-14 spec.