NSN 5935-00-810-3932

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-810-3932

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.032 inches
Bushing Diameter:
0.500 inches
Overall Height:
0.688 inches
Overall Width:
0.688 inches
Environmental Protection:
Watertight and salt water resistant and pressure proof
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.500 inches
Distance From Mounting Shoulder To Front Face:
0.625 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
Bnc single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Operating Tempurature Rating:
Between -65.0 degrees celsius and 165.0 degrees celsius

40

Thready Qty Per Inch (tpi):

NSN 5935-00-810-3932

Electrical Receptacle Connector - Page 2 of 2



Inread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0