

View Online at <https://aerobasegroup.com/nsn/5935-00-810-5962>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape quick connect

Overall Length:

1.524 inches

Overall Width:

1.062 inches

Environmental Protection:

Weather resistant

Mounting Facility Thickness:

0.406 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

N all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

18

Thread Size:

1.062 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and nickel all mating ends all contact groupings

Contact Surface Treatment Specification:

Mil-c-25516 military specification single treatment response all mating ends all contact groupings

Contact Material Specification:

Mil-c-25516 military specification single material response all mating ends all contact groupings

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Qq-n-290 federal specification single treatment response

Included Contact Quantity:

1 all mating ends all contact groupings

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial pin all mating ends all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.002 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-25516 spec.