# NSN 5935-00-810-5962

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-810-5962

# Thread Class:

2a

**Thread Direction:** 

Right-hand

## Body Style:

Straight shape quick connect

### **Overall Length:**

1.524 inches

#### **Overall Width:**

1.062 inches

#### **Environmental Protection:**

Weather resistant

#### **Mounting Facility Thickness:**

0.406 inches

#### **Threaded Device Type:**

## Mounting bushing

## Mating End Quantity:

2

## **Contact Position Arrangement Style:**

N all mating ends

## Contact Removability:

Nonremovable all mating ends all contact groupings

#### Shell Type:

Solid

## **Connector Locking Method:**

Bayonet pin

## Thready Qty Per Inch (tpi):

18

## Thread Size:

1.062 inches

## **Contact Material:**

Copper alloy all mating ends all contact groupings

## **Contact Surface Treatment:**

Gold all mating ends all contact groupings and nickel all mating ends all contact groupings

## **Contact Surface Treatment Specification:**

Mil-c-25516 military specification single treatment response all mating ends all contact groupings

## **Contact Material Specification:**

Mil-c-25516 military specification single material response all mating ends all contact groupings

#### Shell Material:

Copper alloy

#### **Shell Surface Treatment:**

Nickel

# NSN 5935-00-810-5962

Connector Adapter - Page 2 of 2



Shell Surface Treatment Specification: Qq-n-290 federal specification single treatment response Included Contact Quantity: 1 all mating ends all contact groupings **Bushing Accommodation Hole Shape:** Round Included Contact Type: Coaxial pin all mating ends all contact groupings **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.002 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-c-25516 spec.