NSN 5935-00-810-7676

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-810-7676

| Center To Center Distance Between Mounting Facilities Parallel To Length: |
|--|
| 2.282 inches |
| Overall Height: |
| 0.859 inches |
| Overall Width: |
| 0.875 inches |
| Body Length: |
| 2.719 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.112 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.469 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 50 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 13.0 single mating end single contact grouping |
| Polarization Method: |
| Jackscrew |
| Connector Locking Method: |
| Jackscrew-socket |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Insert Material Specification: |
| Mil-m-14, type sdg-f military specification single material response single mating end |
| Included Contact Quantity: |
| 50 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

NSN 5935-00-810-7676

Electrical Receptacle Connector - Page 2 of 2



Mil-std (military Standard):

Mil-m-14 spec.