NSN 5935-00-810-7870

Body Style:

Overall Length:

Straight shape threaded

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-810-7870

•	verali Lengtii.
1.	500 inches
0	verall Diameter:
1.	812 inches
Eı	nvironmental Protection:
Pr	ressure proof
Di	stance From Mounting Shoulder To Front Face:
1.	219 inches
M	ounting Facility Thickness:
0.	250 inches
Tł	readed Device Type:
M	ounting bushing
M	ating End Quantity:
1	
C	ontact Position Arrangement Style:
36	6-2011-46 single mating end
C	ontact Removability:
No	onremovable single mating end single contact grouping
C	ontact Maximum Current Rating In Amps:
40	0.0 single mating end single contact grouping
C	ontact Maximum Ac Voltage Rating In Volts:
50	00.0 single mating end single contact grouping
C	ontact Maximum Dc Voltage Rating In Volts:
70	00.0 single mating end single contact grouping
Po	plarization Method:
Ke	ey, multiple key groove
In	sert Position In Deg:
0.	0
SI	nell Type:
So	olid
C	onnector Locking Method:
E	cternally threaded shell
Te	erminal Location:
Ва	ack single mating end single contact grouping
C	ontact Material:
Co	opper alloy single mating end single contact grouping
C	ontact Surface Treatment:
Si	lver single mating end single contact grouping
In	sert Material:
Rı	ubber single mating end

NSN 5935-00-810-7870

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:	
Solder well single mating end single contact grouping	
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Cadmium	
Included Contact Quantity:	
27 single mating end single contact grouping	
Bushing Accommodation Hole Shape:	
Round	
Included Contact Type:	
Round pin single mating end single contact grouping	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	