

View Online at <https://aerobasegroup.com/nsn/5935-00-811-0579>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

Between 1.365 inches and 1.385 inches

Overall Height:

Between 4.240 inches and 4.260 inches

Overall Width:

Between 3.365 inches and 3.385 inches

Environmental Protection:

Moisture resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.995 inches and 1.005 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 3.035 inches and 3.045 inches

Distance From Mounting Shoulder To Front Face:

Between 0.802 inches and 0.822 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

A45 all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

30.0 2nd mating end 3rd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

10.0 2nd mating end 4th contact grouping

Shell Type:

Solid

Connector Locking Method:

Screw

Thready Qty Per Inch (tpi):

12

Thread Size:

0.312 inches

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Iron 1st mating end 2nd contact grouping

Contact Surface Treatment:

Gold 2nd mating end 4th contact grouping

Insert Material:

Plastic all mating ends and silicon all mating ends

Terminal Type:

Solder well all mating ends all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Type:

Round socket all mating ends all contact groupings

Special Features:

Polarized at position y

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.164 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0