NSN 5935-00-811-1382

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-811-1382

Body Style:
Straight shape
Overall Length:
2.088 inches
Overall Height:
0.660 inches
Overall Width:
0.494 inches
Unthreaded Mounting Hole Diameter:
Between 0.189 inches and 0.190 inches
Distance Between Mounting Facility Centers:
1.852 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
13w3 single mating end
Contact Removability:
Nonremovable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
425.0 single mating end 1st contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end 1st contact grouping
Terminal Type:
Solder well single mating end 1st contact grouping
Shell Material:
Stainless steel

NSN 5935-00-811-1382

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Cadmium and chromate **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification 1st treatment response **Shell Material Specification: Insert Material Specification:**

Qq-s-698 federal specification single material response

Mil-m-14, ty sdg or gdi-30f military specification single material response single mating end

Included Contact Quantity:

10 single mating end 1st contact grouping

Included Contact Type:

Round pin single mating end 1st contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.