NSN 5935-00-811-7855

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-811-7855

Overa	II Le	ngth:

Between 1.312 inches and 1.344 inches

Overall Height:

Between 0.484 inches and 0.516 inches

Overall Width:

Between 0.468 inches and 0.532 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

2925.0 single mating end single contact grouping

Polarization Method:

Contact

Connector Locking Method:

Screw

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Pin single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type mdg military specification single material response single mating end

Included Contact Quantity:

7 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Test Data Document:

10001-2041376 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5935-00-811-7855

Electrical Receptacle Connector - Page 2 of 2



Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.