

View Online at <https://aerobasegroup.com/nsn/5935-00-811-8617>

Body Style:

Straight edge type w/mounting flange

Overall Length:

4.360 inches

Overall Height:

0.740 inches

Overall Width:

Between 0.333 inches and 0.353 inches

Unthreaded Mounting Hole Diameter:

Between 0.125 inches and 0.131 inches

Distance Between Mounting Facility Centers:

Between 4.021 inches and 4.041 inches

Board Accommodated Length:

3.588 inches single board and 3.604 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic phenolic single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-p-19833, type gd1-30 military specification single material response single mating end

Included Contact Quantity:

22 single mating end single contact grouping

Included Contact Type:

Spring pincers single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.022 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.