

View Online at <https://aerobasegroup.com/nsn/5935-00-812-1264>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

3.724 inches

**Overall Height:**

0.716 inches

**Overall Width:**

0.333 inches

**Distance Between Mounting Facility Centers:**

3.466 inches

**Board Accommodated Length:**

2.953 inches single board

**Threaded Device Type:**

Mounting hole

**Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bridged contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

10.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

2400.0 single mating end single contact grouping

**Polarization Method:**

Contact to contact polarizing keys

**Thread Length:**

0.328 inches

**Thread Size:**

0.112 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, type sdc-f military specification single material response single mating end

**Included Contact Quantity:**

18 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Spring pincers single mating end single contact grouping

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.