

View Online at <https://aerobasegroup.com/nsn/5935-00-812-6290>

Body Style:

Straight shape

Overall Length:

1.072 inches

Overall Height:

Between 1.118 inches and 1.132 inches

Overall Width:

Between 2.297 inches and 2.327 inches

Unthreaded Mounting Hole Diameter:

Between 0.117 inches and 0.123 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.744 inches and 0.756 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.056 inches and 2.068 inches

Distance From Mounting Shoulder To Front Face:

Between 0.744 inches and 0.756 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

40 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Included Contact Quantity:

40 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.040 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.