
NSN 5935-00-813-1681

Tip Jack - Page 1 of 2





Thread Class: 2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Red **Body Style:** Threaded bushing mounted thick panel **Overall Length:** 0.906 inches Mounting Bushing Length: 0.469 inches **Body Length:** 0.657 inches **Overall Diameter:** 0.438 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger Finger Accommodation Length: 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.312 inches **Capacitance In Picofarads:** 5.0 **Current Rating In Amps:** 15.0 Mounting Facility Type And Quantity: 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.312 inches **Terminal Type:** Tab, solder lug

NSN 5935-00-813-1681

Tip Jack - Page 2 of 2

Material: Plastic, polyamide insulator Material: Plastic polyamide insulator Surface Treatment: Cadmium terminal Surface Treatment: Cadmium terminal **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A03400

