## NSN 5935-00-813-5874

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-813-5874 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Orange **Body Style:** Threaded bushing mounted **Overall Length:** Between 0.922 inches and 1.000 inches **Body Length:** Between 0.500 inches and 0.672 inches **Overall Diameter:** 0.406 inches **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 2000.0 ac **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger **Finger Accommodation Length:** 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches Thread Length: 0.406 inches **Current Rating In Amps: Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches **Terminal Type:** Turret

Material:
Copper alloy terminal

## NSN 5935-00-813-5874

Tip Jack - Page 2 of 2



Material:
Plastic polyamide insulator
Precious Material And Location:
Spring and terminal surfaces gold
Precious Material:
Gold
Surface Treatment:
Gold terminal
Surface Treatment:
Gold spring
Test Data Document:
81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-39024/10 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03400