NSN 5935-00-813-7279

Plug-in Electronic Components Socket - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-813-7279



Body Material: Plastic **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Top mount w/studs **Fabrication Method:** Molded **Overall Length:** Between 1.420 inches and 1.460 inches **Tempurature Rating:** -65.0 degrees celsius and 125.0 degrees celsius **Overall Height:** Between 0.710 inches and 0.750 inches **Overall Width:** Between 0.590 inches and 0.630 inches **Mounting Hole Diameter:** Between 0.102 inches and 0.122 inches **Body Mounting Hole Accommodation Length:** Between 0.970 inches and 0.990 inches **Body Mounting Hole Accommodation Width:** Between 0.590 inches and 0.630 inches **Mounting Hole Style:** Rectangular, w/four mounting holes/slots **Specific Equipment Accommodated: Contact Maximum Current Rating In Amps:** 3.0 **Contact Material:** Phosphor bronze **Contact Surface Treatment:** Gold and silver **Accommodated Contact Quantity:** Center To Center Distance Between Outside Mounting Holes Along Length: Between 0.390 inches and 0.410 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 1.190 inches and 1.210 inches

Polarization Type:

Colored dot

NSN 5935-00-813-7279

Plug-in Electronic Components Socket - Page 2 of 2



Projection Length Below Mounting Surface:
Between 0.260 inches and 0.300 inches
Mounting Method:
Threaded stud
Mounting Type For Which Designed:
Chassis
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Contact Position Arrangement Style:
Symmetrical
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.014 gold grains, troy and 0.014 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Furnished Items And Quantity:
4 nut and 4 lock washer and 4 stud
Terminal Type And Quantity:
14 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: