

View Online at <https://aerobasegroup.com/nsn/5935-00-813-7279>

Body Material:

Plastic

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Top mount w/studs

Fabrication Method:

Molded

Overall Length:

Between 1.420 inches and 1.460 inches

Tempurature Rating:

-65.0 degrees celsius and 125.0 degrees celsius

Overall Height:

Between 0.710 inches and 0.750 inches

Overall Width:

Between 0.590 inches and 0.630 inches

Mounting Hole Diameter:

Between 0.102 inches and 0.122 inches

Body Mounting Hole Accommodation Length:

Between 0.970 inches and 0.990 inches

Body Mounting Hole Accommodation Width:

Between 0.590 inches and 0.630 inches

Mounting Hole Style:

Rectangular, w/four mounting holes/slots

Specific Equipment Accommodated:

Relay

Contact Maximum Current Rating In Amps:

3.0

Contact Material:

Phosphor bronze

Contact Surface Treatment:

Gold and silver

Accommodated Contact Quantity:

14

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 0.390 inches and 0.410 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 1.190 inches and 1.210 inches

Polarization Type:

Colored dot

Projection Length Below Mounting Surface:

Between 0.260 inches and 0.300 inches

Mounting Method:

Threaded stud

Mounting Type For Which Designed:

Chassis

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Contact Position Arrangement Style:

Symmetrical

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.014 gold grains, troy and 0.014 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Furnished Items And Quantity:

4 nut and 4 lock washer and 4 stud

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300