Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-813-9712

Body Style:

Straight shape, flange mount, external coupling

Overall Length:

1.438 inches

Overall Height:

Between 1.109 inches and 1.141 inches

Overall Width:

Between 1.109 inches and 1.141 inches

Environmental Protection:

Pressure proof

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.906 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.906 inches

Distance From Mounting Shoulder To Front Face:

Between 0.431 inches and 0.441 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

14-15 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end 1st contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end all contact groupings

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Potting type

Terminal Location:

Back single mating end all contact groupings

Electrical Receptacle Connector - Page 2 of 2



Contact Material: Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Plastic single mating end and rubber single mating end **Terminal Type:** Solder well single mating end all contact groupings Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2 federal specification single treatment response **Included Contact Quantity:** 14 single mating end 1st contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.015 gold grains, troy and 0.015 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0