

View Online at <https://aerobasegroup.com/nsn/5935-00-814-0298>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Angle shape, w/o cable clamp

**Overall Diameter:**

1.125 inches

**Body Angle In Deg:**

90.0

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

12s-3 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

145.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring

**Distance From Centerline To Connector End:**

2.451 inches

**Distance From Centerline To Cable End:**

1.500 inches

**Thread Length:**

0.375 inches and 0.375 inches

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thready Qty Per Inch (tpi):**

24 and 20

**Thread Size:**

0.625 inches and 0.750 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, grade b military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1, grade e federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses

**Included Contact Quantity:**

2 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.002 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef and unef

**Specification Data:**

96906-ms3108 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.