Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-814-9004

Thread Class:	
2b	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, external coupling	
Overall Length:	
Between 0.829 inches and 1.047 inches	
Overall Height:	
Between 2.859 inches and 2.891 inches	
Overall Width:	
Between 2.859 inches and 2.891 inches	
Unthreaded Mounting Hole Diameter:	
Between 0.164 inches and 0.174 inches	
Center To Center Distance Between Mounting Facilities	Parallel To Height:
Between 2.205 inches and 2.215 inches	
Distance Between Centerlines Of Mounting Facilities Pa	arallel To Body Width:
Between 2.205 inches and 2.215 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.484 inches and 0.516 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
Lk-68 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
10.0 single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
0.0	
Shell Type:	
Solid	
Connector Locking Method:	
Internally threaded shell	
Thready Qty Per Inch (tpi):	
6	
Thread Size:	
2.562 inches	

## NSN 5935-00-814-9004

Electrical Receptacle Connector - Page 2 of 2



Ter	minal Location:
Bad	ck single mating end single contact grouping
Co	ntact Material:
Cop	pper alloy single mating end single contact grouping
Co	ntact Surface Treatment:
Silv	ver single mating end single contact grouping
Ins	ert Material:
Pla	stic single mating end or plastic phenolic single mating end
Со	ntact Surface Treatment Specification:
Qq	-s-365 federal specification single treatment response single mating end single contact grouping
Ter	rminal Type:
Sol	der well single mating end single contact grouping
She	ell Material:
Alu	minum alloy
She	ell Surface Treatment:
Cad	dmium
Inc	luded Contact Quantity:
68 :	single mating end single contact grouping
Inc	luded Contact Type:
Rou	und socket single mating end single contact grouping
Pre	ecious Material And Location:
Cor	ntact surfaces silver
Pre	ecious Material And Weight:
0.0	68 silver grains, troy
Pre	ecious Material:
Silv	/er
Thr	read Series Designator:
Uns	S
She	elf Life:
N/a	1
Uni	it Of Measure:
Dei	militarization:
No	
Fiig	g:
A03	39b0