NSN 5935-00-815-3391

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-815-3391 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.281 inches **Overall Diameter:** 1.391 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 18-11 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1000.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 119.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch **Thread Size:** 1.062 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:**

Cadmium

NSN 5935-00-815-3391

Electrical Plug Connector - Page 2 of 2



Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.011 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-26482 government specification

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A039b0