## NSN 5935-00-816-1380

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-816-1380 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Overall Length:** 1.688 inches **Overall Height:** 1.094 inches **Overall Width:** 1.094 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 24 and 20 **Thread Size:** 0.625 inches and 0.750 inches **Insert Material:** Plastic single mating end **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize

**Included Contact Quantity:** 

2 single mating end single contact grouping

## NSN 5935-00-816-1380

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Type:
----------	---------	-------

Round pin single mating end single contact grouping

**Thread Series Designator:** 

Unef and unef

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0