Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-816-1380

View Online at https://aerobasegroup.com/nsn/5935-00-816-1380
Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Overall Length:
1.688 inches
Overall Height:
1.094 inches
Overall Width:
1.094 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.812 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.812 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
24 and 20
Thread Size:
0.625 inches and 0.750 inches
Insert Material:
Plastic single mating end
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
2 single mating end single contact grouping



Included Contact Type:

Round pin single mating end single contact grouping

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0