NSN 5935-00-817-2716

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-817-2716

Three d Oleran
Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.656 inches
Overall Diameter:
1.656 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
22-55 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
226.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Thread Length:
0.375 inches
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.437 inches and 1.312 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-00-817-2716

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 55 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.055 gold grains, troy and 0.055 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef and unef Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A039b0