NSN 5935-00-817-5817

Thread Class:

Right-hand **Body Style:**

Thread Direction:

Overall Length:

Overall Height:

Overall Width:

Straight edge type w/mounting flange

Between 6.459 inches and 6.479 inches

Between 0.531 inches and 0.571 inches

Between 0.433 inches and 0.443 inches

2b

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-817-5817

Between 0.433 inches and 0.443 inches
Distance Between Mounting Facility Centers:
Between 6.212 inches and 6.226 inches
Board Accommodated Length:
5.756 inches all boards
Threaded Device Type:
Mounting hole
Board Accommodated Width:
Between 0.054 inches and 0.071 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Bridged contacts inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Thread Length:
0.219 inches
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end

NSN 5935-00-817-5817

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-p-19833b military specification single material response single mating end

Included Contact Quantity:

36 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.