# NSN 5935-00-817-5824

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-817-5824 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight edge type w/mounting flange **Overall Length:** 6.469 inches **Overall Height:** 0.551 inches **Overall Width:** 0.438 inches **Distance Between Mounting Facility Centers:** 6.219 inches **Board Accommodated Length:** 5.766 inches single board **Threaded Device Type:** Mounting hole **Board Accommodated Width:** Between 0.054 inches and 0.071 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Bridged contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys Thread Length: 0.219 inches **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** 

Plastic diallyl phthalate single mating end

# NSN 5935-00-817-5824

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Tab, solder lug single mating end single contact grouping

## **Insert Material Specification:**

Mil-p-19833b military specification single material response single mating end

## **Included Contact Quantity:**

36 single mating end single contact grouping

#### **Included Contact Type:**

Bifurcated spring single mating end single contact grouping

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.