NSN 5935-00-817-5831

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-817-5831

| Thread Class |
|--|
| Thread Class: |
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight edge type w/mounting flange |
| Overall Length: |
| 6.469 inches |
| Overall Height: |
| 0.551 inches |
| Overall Width: |
| 0.438 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.089 inches |
| Distance Between Mounting Facility Centers: |
| 6.219 inches |
| Threaded Device Type: |
| Mounting hole |
| Board Accommodated Width: |
| Between 0.054 inches and 0.071 inches |
| Mating End Quantity: |
| 1 |
| Polarization Method: |
| Contact to contact polarizing keys |
| Thread Length: |
| 0.219 inches |
| Thread Size: |
| 0.112 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Tab, solder lug single mating end single contact grouping |
| Insert Material Specification: |

mocre material opcomoduon

Mil-p-19833b military specification single material response single mating end

NSN 5935-00-817-5831

Electrical Receptacle Connector - Page 2 of 2



| Included | Contact | Quantity: |
|----------|---------|-----------|
|----------|---------|-----------|

36 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.