Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-817-5833

| Thread Class:<br>2b                                    |
|--|
| 26   |
| 20   |
| Thread Direction:                                      |
| Right-hand   |
| Body Style:  |
| Straight edge type w/mounting flange                   |
| Overall Length:  |
| 6.469 inches   |
| Overall Height:  |
| 0.551 inches   |
| Overall Width:   |
| 0.438 inches   |
| Unthreaded Mounting Hole Diameter:                     |
| 0.089 inches   |
| Distance Between Mounting Facility Centers:            |
| 6.219 inches   |
| Board Accommodated Length:                             |
| 5.766 inches single board                              |
| Threaded Device Type:                                  |
| Mounting hole  |
| Board Accommodated Width:                              |
| Between 0.054 inches and 0.071 inches                  |
| Mating End Quantity:                                   |
| 1  |
| Contact Position Arrangement Style:                    |
| Bridged contacts inserted board single mating end      |
| Contact Removability:                                  |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps:                |
| 10.0 single mating end single contact grouping         |
| Polarization Method:                                   |
| Contact to contact polarizing keys                     |
| Thread Length:   |
| 0.219 inches   |
| Thready Qty Per Inch (tpi):                            |
| 40   |
| Thread Size:   |
| 0.112 inches   |
| Terminal Location:                                     |
| Back single mating end single contact grouping         |
| Contact Material:                                      |
| Copper alloy single mating end single contact grouping |



| Gold single mat    | ting end single contact grouping  |
|--------------------|---|
| Insert Material    | :   |
| Plastic diallyl ph | nthalate single mating end  |
| Contact Surfac     | ce Treatment Specification:   |
| Mil-g-45204, typ   | pe 2, cl 1 military specification single treatment response single mating end single contact grouping |
| Terminal Type      | :   |
| Tab, solder lug    | single mating end single contact grouping   |
| Insert Material    | Specification:  |
| Mil-p-19833b m     | ilitary specification single material response single mating end                                      |
| Included Conta     | act Quantity:   |
| 36 single mating   | g end single contact grouping   |
| Included Conta     | act Type:   |
| Bifurcated sprin   | ig single mating end single contact grouping  |
| Precious Mate      | rial And Location:  |
| Contact surface    | es gold   |
| Precious Mate      | rial And Weight:  |
| 0.036 gold grair   | ns, troy  |
| Precious Mate      | rial:   |
| Gold               |   |
| Thread Series      | Designator:   |
| Unc                |   |
| Shelf Life:        |   |
| N/a                |   |
| Unit Of Measu      | re:   |
|                    |   |
| Demilitarizatio    | n:  |
| No                 |   |
| Fiig:              |   |
| A039b0             |   |
| Mil-std (militar   | y Standard):  |
| Mil-g-45204 spe    | ec.   |