Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-817-8131

Thread Class: 2g **Thread Pitch Diameters:** +0.190/+0.200 inches Thread Direction: **Right-hand Environmental Protection:** Moisture resistant **Threaded Device Type:** Coupling facility Mating End Quantity: 1 **Contact Position Arrangement Style:** 16-10 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 single mating end all contact groupings **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 5 **Thread Size:** 1.000 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Plastic polyamide single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy



Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
7 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Special Features:
Flange mount
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.010 gold grains, troy and 0.010 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0