Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-817-8619

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight edge type w/mounting flange
Overall Length:
6.469 inches
Overall Height:
0.551 inches
Overall Width:
0.438 inches
Unthreaded Mounting Hole Diameter:
0.089 inches
Distance Between Mounting Facility Centers:
6.219 inches
Board Accommodated Length:
5.766 inches single board
Threaded Device Type:
Mounting hole
Board Accommodated Width:
Between 0.054 inches and 0.071 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Bridged contacts inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Thread Length:
0.219 inches
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping



Gold single mati	ng end single contact grouping
Insert Material:	
Plastic diallyl phi	thalate single mating end
Contact Surface	e Treatment Specification:
Mil-g-45204, typ	e 2, cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:	
Tab, solder lug :	single mating end single contact grouping
Insert Material S	Specification:
Mil-p-19833b mil	litary specification single material response single mating end
Included Conta	ct Quantity:
36 single mating	end single contact grouping
Included Conta	ct Type:
Bifurcated spring	g single mating end single contact grouping
Precious Materi	ial And Location:
Contact surfaces	s gold
Precious Materi	ial And Weight:
0.036 gold grains	s, troy
Precious Materi	ial:
Gold	
Thread Series D	Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Measure	e:
Demilitarization	
No	
Fiig:	
A039b0	
Mil-std (military	y Standard):
Mil-g-45204 spee	с.