Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-818-3768

# Thread Class:

2a

**Thread Direction:** 

Right-hand

#### **Body Style:**

Straight shape threaded

#### **Overall Length:**

0.703 inches

#### **Overall Diameter:**

0.281 inches

## **Threaded Device Type:**

Mounting bushing

## Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

Nonstd single mating end

## **Contact Removability:**

Nonremovable single mating end single contact grouping

#### Shell Type:

Solid

## **Connector Locking Method:**

Spring friction

## Radio Frequency Type Contact Characteristic Impedance In Ohms:

93.0 single mating end single contact grouping

#### **Thread Size:**

0.216 inches

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Silver single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# **Insert Material:**

Plastic tetrafluoroethylene single mating end

# **Terminal Type:**

Solder well single mating end single contact grouping

# Shell Material:

Copper alloy

# Shell Surface Treatment:

Silver

# Shell Material Specification:

Qq-b626, comp 22 federal specification single material response

# NSN 5935-00-818-3768

Electrical Receptacle Connector - Page 2 of 2



**Included Contact Quantity:** 1 single mating end single contact grouping Included Contact Type: Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold and contact and shell surface silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.005 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0