NSN 5935-00-818-4385

Thread Class:

Right-hand

Body Style:

Straight shape

Overall Length:

Thread Direction:

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-818-4385

Between 2.895 inches and 2.905 inches
Overall Height:
0.810 inches
Overall Width:
Between 0.355 inches and 0.365 inches
Environmental Protection:
Moisture proof and vibration resistant
Distance Between Mounting Facility Centers:
Between 2.595 inches and 2.605 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
23 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
840.0 single mating end single contact grouping
Polarization Method:
Contact
Thread Length:
0.230 inches and 0.270 inches
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic melamine single mating end

NSN 5935-00-818-4385

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type mme military specification single material response single mating end

Included Contact Quantity:

23 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.023 gold grains, troy and 0.023 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.