## NSN 5935-00-818-6560

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-818-6560

3· · · · · · · · · · · · · · · · · · ·
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Angle, shape, internal coupling
Overall Length:
1.938 inches
Overall Height:
1.297 inches
Overall Diameter:
0.812 inches
Environmental Protection:
Corrosion resistant and cold resistant and heat resistant and moisture resistant and shock resistant and vibration resistant and weatherproo
Cable Entrance Diameter:
Between 0.405 inches and 0.430 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
N single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Crimp type
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment

Silver single mating end single contact grouping

## **NSN 5935-00-818-6560**Electrical Plug Connector - Page 2 of 2



Insert Material:
Plastic polytetrafluoroethylene single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Copper alloy
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surface silver
Precious Material And Weight:
0.005 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0