

View Online at <https://aerobasegroup.com/nsn/5935-00-818-7891>

Body Style:

Straight shape, internal coupling

Overall Length:

0.750 inches

Overall Diameter:

0.390 inches

Cable Entrance Diameter:

Between 0.090 inches and 0.115 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 120.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Compression nut

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Metal single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Metal

Shell Surface Treatment:

Gold and silver

Shell Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response and qq-s-365 federal specification 2nd treatment response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact and body surfaces gold and contact and body surfaces silver

Precious Material And Weight:

0.105 gold grains, troy and 0.105 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.